

# DuPont™ Hytrel® 4068FG

## THERMOPLASTIC POLYESTER ELASTOMER

### Product Information

Common features of Hytrel® thermoplastic polyester elastomer include mechanical and physical properties such as exceptional toughness and resilience, high resistance to creep, impact and flex fatigue, flexibility at low temperatures and good retention of properties at elevated temperatures. In addition, it resists many industrial chemicals, oils and solvents. Special grades include heat stabilised, flame retardant, food contact compliant, blow molding and extrusion grades. Concentrates offered include black pigments, UV protection additives, heat stabilisers, and flame retardants.

Hytrel® thermoplastic polyester elastomer is plasticiser free.

The good melt stability of Hytrel® thermoplastic polyester elastomer normally enables the recycling of properly handled production waste. If recycling is not possible, DuPont recommends, as the preferred option, incineration with energy recovery (-24 kJ/g of base polymer) in appropriately equipped installations.

For disposal, local regulations have to be observed.

Hytrel® thermoplastic polyester elastomer typically is used in demanding applications in the automotive, fluid power, electrical/electronic, consumer goods, appliance and power tool, sporting goods, furniture, industrial and off-road transportation/equipment industry.

### Hytrel® 4068FG is a high performance thermoplastic polyester elastomer developed for applications in contact with food.

#### FOOD CONTACT

This product is manufactured according to Good Manufacturing Practice (GMP) principles and generally accepted in food contact applications in Europe and the USA when meeting applicable use conditions. For details, individual compliance statements are available from your DuPont representative.

General information	Value	Unit	Test Standard
Resin Identification	TPC-ET	-	ISO 1043
Part Marking Code	>TPC-ET<	-	ISO 11469
Rheological properties	Value	Unit	Test Standard
Melt volume-flow rate	8.8	cm <sup>3</sup> /10min	ISO 1133
Temperature	220	°C	ISO 1133
Load	2.16	kg	ISO 1133
Melt mass-flow rate	8.5	g/10min	ISO 1133
Melt mass-flow rate, Temperature	220	°C	ISO 1133
Melt mass-flow rate, Load	2.16	kg	ISO 1133
Molding shrinkage, parallel	1.0	%	ISO 294-4, 2577
Molding shrinkage, normal	0.9	%	ISO 294-4, 2577
Mechanical properties (TPE)	Value	Unit	Test Standard
Tensile Modulus	45	MPa	ISO 527-1/-2
Stress at 5% strain	2.4	MPa	ISO 527-1/-2
Stress at 10% strain	3.5	MPa	ISO 527-1/-2
Stress at 50% strain	6.7	MPa	ISO 527-1/-2
Stress at break	29	MPa	ISO 527-1/-2
Strain at break	>300	%	ISO 527-1/-2
Nominal strain at break	800	%	ISO 527-1/-2
Tear strength, parallel	100	kN/m	ISO 34-1
Tear strength, normal	103	kN/m	ISO 34-1
Abrasion resistance	180	mm <sup>3</sup>	ISO 4649
Shore D hardness, max	37	-	ISO 7619-1
Shore D hardness, 15s	33	-	ISO 7619-1
Mechanical properties	Value	Unit	Test Standard
Flexural Modulus	47	MPa	ISO 178
Tensile creep modulus			ISO 899-1
1h	28	MPa	
1000h	21	MPa	
Charpy impact strength			ISO 179/1eU
73°F	N	kJ/m <sup>2</sup>	
-22°F	N	kJ/m <sup>2</sup>	

To find out more, visit [DuPont Performance Polymers](#) or contact nearest DuPont location.

North America

Asia Pacific

Europe/Middle East/Africa

DONGGUAN FUMEI PLASTICS CO.,LTD.

TEL: +86 0769-82339888 / 87798999

EMAIL: fumei@foomx.com



# DuPont™ Hytrel® 4068FG

## THERMOPLASTIC POLYESTER ELASTOMER

Charpy notched impact strength			ISO 179/1eA
73°F	N	kJ/m <sup>2</sup>	
-22°F	N	kJ/m <sup>2</sup>	
Tensile notched impact strength, 73°F	145	kJ/m <sup>2</sup>	ISO 8256/1
Izod notched impact strength			ISO 180/1A
73°F	N	kJ/m <sup>2</sup>	
-22°F	N	kJ/m <sup>2</sup>	
-40°F	N	kJ/m <sup>2</sup>	
<b>Thermal properties</b>	<b>Value</b>	<b>Unit</b>	<b>Test Standard</b>
Melting temperature, 18°F/min	193	°C	ISO 11357-1/-3
Glass transition temperature, 18°F/min	-55	°C	ISO 11357-1/-2
Vicat softening temperature, 90°F, 2 lbf	130	°C	ISO 306
Coeff. of linear therm. expansion, parallel	230	E-6/K	ISO 11359-1/-2
Coeff. of linear therm. expansion, normal	230	E-6/K	ISO 11359-1/-2
Eff. thermal diffusivity	5.44E-8	m <sup>2</sup> /s	-
<b>Flammability</b>	<b>Value</b>	<b>Unit</b>	<b>Test Standard</b>
FMVSS Class	B	-	ISO 3795 (FMVSS 302)
Burning rate, Thickness 1 mm	<100	mm/min	ISO 3795 (FMVSS 302)
<b>Electrical properties</b>	<b>Value</b>	<b>Unit</b>	<b>Test Standard</b>
Relative permittivity			IEC 62631-2-1
100Hz	4.8	-	
1MHz	4.7	-	
Electric strength	18	kV/mm	IEC 60243-1
Comparative tracking index	600	-	IEC 60112
<b>Other properties</b>	<b>Value</b>	<b>Unit</b>	<b>Test Standard</b>
Humidity absorption, 80mil	0.3	%	Sim. to ISO 62
Water absorption, 80mil	0.7	%	Sim. to ISO 62
Density	1110	kg/m <sup>3</sup>	ISO 1183
<b>VDA Properties</b>	<b>Value</b>	<b>Unit</b>	<b>Test Standard</b>
Emission of organic compounds	10	µgC/g	VDA 277
Odor test	4	class	VDA 270
<b>Injection</b>	<b>Value</b>	<b>Unit</b>	<b>Test Standard</b>
Drying Recommended	yes	-	-
Drying Temperature	≥100	°C	-
Drying Time, Dehumidified Dryer	2 - 3	h	-
Processing Moisture Content	≤0.08	%	-
Melt Temperature Optimum	225	°C	-
Min. melt temperature	220	°C	-
Max. melt temperature	250	°C	-
Mold Temperature Optimum	40	°C	-
Min. mold temperature	30	°C	-
Max. mold temperature	40	°C	-
<b>Extrusion</b>	<b>Value</b>	<b>Unit</b>	<b>Test Standard</b>
Drying Temperature	90 - 110	°C	-
Drying Time, Dehumidified Dryer	2 - 3	h	-
Processing Moisture Content	≤0.06	%	-
Melt Temperature Optimum	215	°C	-
Melt Temperature Range	210 - 225	°C	-

Characteristics			
Processing	<ul style="list-style-type: none"> <li>• Injection Molding</li> <li>• Film Extrusion</li> <li>• Profile Extrusion</li> </ul>	<ul style="list-style-type: none"> <li>• Sheet Extrusion</li> <li>• Other Extrusion</li> <li>• Casting</li> </ul>	<ul style="list-style-type: none"> <li>• Thermoforming</li> </ul>
Delivery form	<ul style="list-style-type: none"> <li>• Pellets</li> </ul>		
Special characteristics	<ul style="list-style-type: none"> <li>• Light stabilized or stable to light</li> </ul>		

Revised: 2018-03-23

Page: 2 of 6

To find out more, visit [DuPont Performance Polymers](#) or contact nearest DuPont location.

North America

Asia Pacific

Europe/Middle East/Africa

DONGGUAN FUMEI PLASTICS CO.,LTD.

TEL: +86 0769-82339888 / 87798999

EMAIL: fumei@foomx.com

Copyright 2017 DuPont. The DuPont Oval Logo is a trademark or registered trademark of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.



# DuPont™ Hytrel® 4068FG

## THERMOPLASTIC POLYESTER ELASTOMER

Regional Availability

- North America
- Europe

- Asia Pacific
- South and Central America

- Near East/Africa
- Global

### Processing Texts

#### Injection molding

##### PREPROCESSING

Drying temperature = 100°C  
Drying time, dehumidified dryer = 2-3 h  
Processing moisture content = <0.06 %

##### PROCESSING

Melt temperature range = 205-230°C  
Melt temperature optimum = 215°C

#### Profile extrusion

##### PREPROCESSING

Drying temperature = 100°C  
Drying time, dehumidified dryer = 2-3 h  
Processing moisture content = <0.06 %

##### PROCESSING

Melt temperature range = 205-230°C  
Melt temperature optimum = 215°C

#### North America

DONGGUAN FUMEI PLASTICS CO.,LTD.  
EMAIL: fumei@foomx.com

#### Asia Pacific

TEL: +86 0769-82339888 / 87798999

#### Europe/Middle East/Africa




# DuPont™ Hytrel® 4068FG

## THERMOPLASTIC POLYESTER ELASTOMER

Diagrams

Stress-Strain (TPE)



To find out more, visit [DuPont Performance Polymers](#) or contact nearest DuPont location.

North America

DONGGUAN FUMEI PLASTICS CO.,LTD.

EMAIL: fumei@foomx.com

Asia Pacific

TEL: +86 0769-82339888 / 87798999

Europe/Middle East/Africa



# DuPont™ Hytrel® 4068FG

## THERMOPLASTIC POLYESTER ELASTOMER

### Chemical Media Resistance

#### Acids

- ✓ Acetic Acid (5% by mass) (23 °C)
- ✓ Citric Acid solution (10% by mass) (23 °C)
- ✓ Lactic Acid (10% by mass) (23 °C)
- ✗ Hydrochloric Acid (36% by mass) (23 °C)
- ✗ Nitric Acid (40% by mass) (23 °C)
- ✗ Sulfuric Acid (38% by mass) (23 °C)
- ✓ Sulfuric Acid (5% by mass) (23 °C)
- ✗ Chromic Acid solution (40% by mass) (23 °C)

#### Bases

- ✓ Sodium Hydroxide solution (35% by mass) (23 °C)
- ✓ Sodium Hydroxide solution (1% by mass) (23 °C)
- ✓ Ammonium Hydroxide solution (10% by mass) (23 °C)

#### Alcohols

- ✓ Isopropyl alcohol (23 °C)
- ✓ Methanol (23 °C)
- ✓ Ethanol (23 °C)

#### Hydrocarbons

- ✓ n-Hexane (23 °C)
- ✓ Toluene (23 °C)
- ✓ iso-Octane (23 °C)

#### Ketones

- ✗ Acetone (23 °C)

#### Ethers

- ✗ Diethyl ether (23 °C)

#### Mineral oils

- ✓ SAE 10W40 multigrade motor oil (23 °C)
- ✗ SAE 10W40 multigrade motor oil (130 °C)
- ✗ SAE 80/90 hypoid-gear oil (130 °C)
- ✓ Insulating Oil (23 °C)

#### Standard Fuels

- ✗ ISO 1817 Liquid 1 - E5 (60 °C)
- ✗ ISO 1817 Liquid 2 - M15E4 (60 °C)
- ✗ ISO 1817 Liquid 3 - M3E7 (60 °C)
- ✗ ISO 1817 Liquid 4 - M15 (60 °C)
- ✓ Standard fuel without alcohol (pref. ISO 1817 Liquid C) (23 °C)
- ✓ Standard fuel with alcohol (pref. ISO 1817 Liquid 4) (23 °C)



# DuPont™ Hytrel® 4068FG

## THERMOPLASTIC POLYESTER ELASTOMER

- ✓ Diesel fuel (pref. ISO 1817 Liquid F) (23°C)
- ✓ Diesel fuel (pref. ISO 1817 Liquid F) (90°C)
- ✗ Diesel fuel (pref. ISO 1817 Liquid F) (>90°C)

### Salt solutions

- ✓ Sodium Chloride solution (10% by mass) (23°C)
- ✗ Sodium Hypochlorite solution (10% by mass) (23°C)
- ✓ Sodium Carbonate solution (20% by mass) (23°C)
- ✓ Sodium Carbonate solution (2% by mass) (23°C)
- ✓ Zinc Chloride solution (50% by mass) (23°C)

### Other

- ✓ Ethyl Acetate (23°C)
- ✗ Hydrogen peroxide (23°C)
- ✗ DOT No. 4 Brake fluid (130°C)
- ✗ Ethylene Glycol (50% by mass) in water (108°C)
- ✓ 1% nonylphenoxy-polyethyleneoxy ethanol in water (23°C)
- ✓ 50% Oleic acid + 50% Olive Oil (23°C)
- ✓ Water (23°C)
- ✓ Water (90°C)
- ✓ Phenol solution (5% by mass) (23°C)

### Symbols used:

- ✓ possibly resistant

Defined as: Supplier has sufficient indication that contact with chemical can be potentially accepted under the intended use conditions and expected service life. Criteria for assessment have to be indicated (e.g. surface aspect, volume change, property change).

- ✗ not recommended - see explanation

Defined as: Not recommended for general use. However, short-term exposure under certain restricted conditions could be acceptable (e.g. fast cleaning with thorough rinsing, spills, wiping, vapor exposure).

Contact DuPont for Material Safety Data Sheet, general guides and/or additional information about ventilation, handling, purging, drying, etc. ISO Mechanical properties measured at 160 mil (Hytrel® measured at 80 mil), IEC Electrical properties measured at 80 mil, all ASTM properties measured at 120 mil, and test temperatures are 73°F unless otherwise stated.

The information set forth herein is furnished free of charge and is based on technical data that DuPont believes to be reliable and falls within the normal range of properties. It is intended for use by persons having technical skill, at their own discretion and risk. This data should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end-use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents. Caution: Do not use in medical applications involving permanent implantation in the human body. For other medical applications, discuss with your DuPont customer representative and read Medical Caution H-50103-5.

Copyright © 2017 DuPont or its affiliates. All Rights Reserved. The DuPont Oval Logo, DuPont™, The miracles of science™ and all products denoted with ® or ™ are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates.

To find out more, visit [DuPont Performance Polymers](#) or contact nearest DuPont location.

#### North America

DONGGUAN FUMEI PLASTICS CO.,LTD.

EMAIL: fumei@foomx.com

#### Asia Pacific

TEL: +86 0769-82339888 / 87798999

#### Europe/Middle East/Africa

